

## Thermic 200 D

**T.V.** Thermal Valve



**3600**  
RPM



Equipped with:

- Three ceramic pistons, brass linear pump head with built-in by-pass valve.
- 3600 RPM gear box between engine and pump.
- By-pass with thermostatic valve.
- Automatic RPM regulation.
- Electrical start with engine functions control.
- Diesel engine (air cooled) with integrated Diesel tank.
- Integrated regulable detergent suction with external suction probe.
- Pressure regulator.
- Glicerine pressure gauge.
- Heavy duty steel frame.
- Battery included.
- Brass filter.
- Pneumatic effect Ø 260 wheels with brake

### STANDARD EQUIPMENT

- 3.700.0030 Gun M22



- 0.966.0084 Lance M22 high/low pressure.



- 3.103.0208 Nozzle 075 (mod.1621) • 3.103.0111 Nozzle 050 (mod.2016)



- 0.966.0086 High pressure hose R2 10 m (mod.2016)
- 0.966.0011 High pressure hose R2 10 m (mod.1621)



Foam Lance



	Thermic 200 D
code	0 .0 66.0085
operat. pressure	200 bar-3800 psi
delivery rate	1080 l/h
hp	10 hp
RPM	3600 RPM
max. water inlet temp.	60 °C
dimension/weight	95x68x95cm / 124 Kg - 231 lbs