

Windy 278 PF



Equipped with:

- 2 high efficiency by pass motors.
- Suction system with by-pass cooling.
- Filter cleaning system.
- Plastic tank (PP).
- Shock proof trolley.
- Liquid float valve.
- Drain hose system.
- Static electric shock inhibitor.
- 7,5 m power cable.
- Traceless wheels.
- Accessories Ø 40.
- Handy accessory holder.

Standard equipment:

- 5.209.0021 Hose 2,5 m



- 6.205.0126



- 3.754.0048



- 3.754.0049



- 3.754.0083



- 3.754.0084



- 3.754.0085



- 5.509.2176 Cloth filter



- Power cable 7,5 m

Optional:

- 5.212.0022 Paper collector filter set - 10 pcs
- 5.509.1405 Cloth filter for fine dust
- 5.212.0093 Nylon filter
- 5.212.0021 Washable filter
- 5.212.0034 Hepa filter



Watch the video on youtube:
www.youtube.com/lavorpro

	Windy 278 PF
code	8.247.0002
voltage	220-240V ~ 50-60Hz
n°motors - power (max)	2 - 2000 (2400) W High efficiency motor.
column depression	22 kPa/2200 mmH ₂ O
air suction	130 l/s
total volume/dust/liquid	78 l./35 l./48 l.
dimension/weight	62x51x96 cm/21,5 kg